

P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj. Therm. Adj. Mag.



Component type	Power switching circuit breaker
Range	TemBreak PRO
Model	N/A
Product status	Existing

The latest innovation of MCCBs from Terasaki, offering superior performance and versatility.

Rated current I_n	32.0 A
Number of poles	4.0
Max. rated operation voltage U_e AC	690.0 V
Rated ultimate short-circuit breaking capacity I_{cu} at 415 V, 50 Hz	70.0 kA
Rated service short-circuit breaking capacity I_{cs} at 415 V, 50 Hz	50.0 kA
Type of protection trip unit	Thermal/magnetic release
Trip curve	Adj. thermal, adj. magnetic
Frame size rating	160.0 A
Long time overload protection adjustment range	20 - 32 A
Position of connection for main current circuit	Front side
Instantaneous protection adjustment range	192 - 384 A
Rated frequency	50 - 60 Hz
Rated insulation voltage U_i	800.0 V
Suitable for isolation	Yes
Rated short circuit breaking capacity, I_{cu} 690V AC	6.0 kA
Rated short circuit breaking capacity, I_{cs} 690V AC	6.0 kA
Rated impulse withstand voltage U_{imp}	8.0 kV
Over voltage category	IV
Reverse connection of supply possible	Yes
AC power loss per pole at I_n	9.0 W
Electrical life at U_n , I_n (service cycles)	30000.0 cycles
Type of electrical connection of main circuit	Screw connection
Power loss at rated current	27.0 W

ELECTRICAL

P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj.
Therm. Adj. Mag.



TERASAKI
Innovators in Protection Technology


MECHANICAL	Connectable conductor cross section	1.5 - 70 mm ²
	DIN rail (top hat rail) mounting optional	Yes
	Mechanical life (service cycles)	50000.0 cycles
	Vibration acceleration (Max)	19.0 m/s ²
	Vibration frequency, operational (Max)	16.7 Hz
	Vibration duration (Max)	12.0 min
DIMENSIONS	Height	130.0 mm
	Width	120.0 mm
	Pole connection pitch	30.0 mm
	Built-in depth	68.0 mm
	Depth (toggle included)	95.5 mm
	Weight	1.3 kg
ENVIRONMENT	Pollution degree	3.0
	Rated surrounding temperature without derating	50.0 °C
	Ambient temperature during operating	-5 - 70 °C
	Max. temperature	70.0 °C
	Storage temperature	-10 - 70 °C
	Allowable relative humidity	0 - 85 %
Altitude before derating (Max)	2000.0 m	
CERTIFICATES/APPROVALS	Standard	AS/NZS IEC 60947.2

P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj. Therm. Adj. Mag.




DIMENSIONAL DIAGRAM



Panel cutout (top view)

for Cutout B

Panel cutout dimensions shown give an allowance of 1.0 mm or more around the handle escutcheon



(*2) Cutout 52 mm for 2 pole MCCBs

Preparation of conductor





Table for square hole for connector on LSI version

Type of OCR for LSI version	A pole (PAP)		C/N pole (ECP)	
	3P	4P	3P	4P
LSI	Hole	Hole	no	no
LSIG	Hole	Hole	Hole	no

Drilling plan (top view)



P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj. Therm. Adj. Mag.



RELATED PRODUCTS

ACCESSORY



Item No: T2AL00LML3STA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for A and P Models 1 CO Contact Left Side Mounting General Type

Item No: T2AL00LML3SWA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for A and P Models 1 CO Contact Left Side Mounting Wired Type

Item No: T2AX00LML3RWA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 CO Contact Micro Switch Wired Type

Item No: T2AX00LML3STA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 CO Contact General Type

Item No: T2AX00LML3SWA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 NO Contact 1 NC Contact Wired Type

Item No: T2BA16L3SH

Required: No

Description: Terasaki TemBreak PRO Interpole Barriers for A160/P160 Qty 2

Item No: T2CF253WC

Required: No

Description: Terasaki TemBreak 2 Terminal Screen Front Connect for E250/S250 3P MCCBs

Item No: T2HL25L

Required: No

Description: Terasaki TemBreak PRO Non Captive Toggle Lock 5 x 16.5mm Slot for A160/A250/P160/P250

Item No: T2HS250SHAFT

Required: No

Description: Terasaki TemBreak 2 Handle Shaft 90mm for 125/250 MCCBs



Item No: T2HSESC100

Required: No

Description: Terasaki TemBreak 2 Handle Label Plate 100mm MCCBs

Item No: T2SH00LA10T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 110V AC

Item No: T2SH00LA10WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 110-120V AC Wired Type

Item No: T2SH00LA20T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 230-240V AC

Item No: T2SH00LA40T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 400-415V AC

Item No: T2SH00LA40WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 380-450V AC Wired Type

Item No: T2SH00LD02T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 24V DC

Item No: T2SH00LD02WA








Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 24V DC Wired Type

Item No: T2SH00LD04WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 48V DC Wired Type



P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj. Therm. Adj. Mag.



RELATED PRODUCTS

ACCESSORY



Item No: T2SH00LD10WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 110-120V DC Wired Type



Item No: T2SH00LD20WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 200-240V DC Wired Type



Item No: T2UV00LA10NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 100-120V AC Wired Type



Item No: T2UV00LA20NT

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 230 to 240V AC



Item No: T2UV00LA20NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 200-240V AC Wired Type



Item No: T2UV00LA40NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 380-450V AC Wired Type



Item No: T2UV00LD02NT

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 24V DC



Item No: T2UV00LD02NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 24V DC Wired Type



Item No: T2UV00LD10NWA

Required: No


Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 100-120V DC Wired Type



Item No: T2UV00LD20NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 200-240V DC Wired Type



Item No: TPCF164SLEPH


Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style with Barrier for 4P P160 MCCB Qty 1

Item No: TPCF164SLNP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CF Long Style for 4P P160 MCCB Qty 2



Item No: TPCF164SLNPH

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style for 4P P160 MCCB Qty 1



Item No: TPCF164SSEPH

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Short Style with Barrier for 4P P160 MCCB Qty 2



Item No: TPCF164SSNP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Short Style for 4P P160 MCCB Qty 2



Item No: TPCF16SL

Required: No


Description: Terasaki TemBreak PRO Terminal Cover Clip for P160



Item No: TPCLCP16

Required: No

Description: Terasaki TemBreak PRO Captive Lock Cover for P160 Thermal Magnetic and Basic Electronic MCCB



Item No: TPCLCP16SE

Required: No

Description: Terasaki TemBreak PRO Captive Lock Cover for P160 Smart Electronic MCCB

P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj. Therm. Adj. Mag.



RELATED PRODUCTS

ACCESSORY



Item No: TPCR164SP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CR Flush Style for P160 4P MCCB Qty 2



Item No: TPCR164SPH

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CR Flush Style for P160 4P MCCB Qty 1



Item No: TPCS164SPB

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CS Standard Style for P160 4P MCCB Qty 2



Item No: TPDA16SA

Required: No

Description: Terasaki TemBreak PRO DIN Rail Adaptor for P160 MCCB



Item No: TPFW16S4L1H

Required: No

Description: Terasaki TemBreak PRO Tunnel Terminal fits 35 to 120mm² for P160 Qty 4



Item No: TPFW16S4L6H

Required: No

Description: Terasaki TemBreak PRO Tunnel Terminal fits 6 Cables 4 to 25mm² for P160 Qty 4



Item No: TPHB165UR5BN

Required: No

Description: Terasaki TemBreak PRO Handle Direct Mount with Door Interlock for P160 Black



Item No: TPHP16SR6BN

Required: No

Description: Terasaki TemBreak PRO HP Handle with 421mm Extension Shaft IP65 for P160 Grey



Item No: TPHP16SR6RN

Required: No


Description: Terasaki TemBreak PRO HP Handle with 421mm Extension Shaft IP65 for P160 Red



Item No: TPHS16R5GM

Required: No

Description: Terasaki TemBreak PRO HS Handle with 356mm Extension Shaft IP55 for P160 MCCB Grey



Item No: TPHS16R5RM

Required: No

Description: Terasaki TemBreak PRO HS Handle with 356mm Extension Shaft IP55 for P160 MCCB Red



Item No: TPMC25SA10N

Required: No

Description: Terasaki TemBreak PRO Motor 110V AC for P160/P250



Item No: TPMC25SA24N

Required: No

Description: Terasaki TemBreak PRO Motor 230-240V AC for P160/P250



Item No: TPMC25SD02N

Required: No

Description: Terasaki TemBreak PRO Motor 24V DC for P160/P250



Item No: TPMC25SD04N

Required: No

Description: Terasaki TemBreak PRO Motor 48V DC for P160/P250



Item No: TPMC25SD10N

Required: No

Description: Terasaki TemBreak PRO Motor 110V DC for P160/P250



Item No: TPMC25SD20N

Required: No

Description: Terasaki TemBreak PRO Motor 220V DC for P160/P250



Item No: TPML16SL4

Required: No

Description: Terasaki TemBreak PRO Front Link Interlock Left Side Mount for 4P P160 MCCB





P160H2432TM

Terasaki TemBreak PRO MCCB 160 Frame 70kA 4P 32A Adj. Therm. Adj. Mag.



RELATED PRODUCTS

ACCESSORY

	<p>Item No: TPMW00L Required: No Description: Terasaki TemBreak PRO Interlock Wire 1.5m for P Model MCCBs</p>		<p>Item No: TPMW16SCN Required: No Description: Terasaki TemBreak PRO Cable Interlock Kit without Wire for P160</p>
	<p>Item No: TPMW00S Required: No Description: Terasaki TemBreak PRO Interlock Wire 1.0m for P Model MCCBs</p>		<p>Item No: TPRP164SH Required: No Description: Terasaki TemBreak PRO Rear Connect Studs for 4P P160 MCCB Half Set</p>